

Alliance

series
modular kiosk



Slim, Contemporary, Modular Design Compliments a Wide Variety of Business Environments.

Wide Variety of Options for Virtually any Customer Need

Robust Design Supports Deployment into Multiple Environments

Customizable and Brandable Graphic Surfaces

Multiple Freestanding Configurations Available

Designed for Ease of Use and Accessibility for the Disabled

5point

Alliance

series
modular kiosk

STANDARD FEATURES

- Slim Contemporary Modular Design
- All Metal Freestanding Enclosure with Keylock
- Small Form Factor PC Support (multiple options available)
- Open Frame LCD Support
- Standard Graphics Header
- Multiple Color and Finish Options

AVAILABLE OPTIONS

- Open Frame TFT LCD, 15", 17" or 19"
- Touch Screen (5-Wire Resistive, Capacitive, Surface Acoustic Wave and Vandal Resistant)
- Privacy Filter
- Audio Amplifier & Speakers
- Industrial Keyboard and Trackball
- Direct Thermal Receipt Printer w/ Presenter
- Direct Thermal Full Page Printer w/ Presenter & Retraction
- Laser Printer Support (Multiple Options)
- ADA Compliant Amplified Telephone Handset (analog POTS or VoIP)
- Digital Camera & Video
- 802.11b/g Wireless LAN
- Card Dispenser
- Magnetic Card Reader, 3-Track ISO, Smart Card
- Currency Acceptor
- Encrypted Keypad
- Bar Code Scanner
- Secondary Attract Monitor
- Uninterruptible Power Supply
- Other Features and Options Available

PHYSICAL SPECIFICATIONS

Height Slim 61.57" / 176.4cm **Medium** 61.57" / 176.4cm

Height Header 75" / 109.5cm **Attract Monitor** 89" / 226.1cm

Width Slim 20" / 50.8cm **Medium** 20" / 50.8cm

Depth Slim 12.54" / 31.9cm **Medium** 20" / 50.8cm

Base Slim 22.5" / 57.2cm Wide by 18" / 45.7cm Deep

Base Medium 22.5" / 57.2cm Wide By 20" / 50.8cm Deep

Weight 260 lbs. / 118.8 Kg *depending on configuration

Shipping Weight 305 lbs. / 138.6 Kg *depending on configuration

ELECTRICAL SPECIFICATIONS

Electrical requirements

100-127VAC ~ 50/60 Hz, 5.0A

200-240VAC ~ 50/60 Hz, 2.5A

Operating temperature

32 F – 115 F Degrees

0 C – 45 C Degrees

Operating Humidity

20% – 95% Relative Humidity (non-condensing)

5point

825 Bellbrook Ave.

937.374.3193 | voice

info@5point.com

Xenia, Ohio 45385 USA

866.266.3104 | fax

www.5point.com